




1019.95 EUR

incl. 19% VAT, plus [shipping](#)

- Dual LAN !
- 4x COM !
- 8-24V DC input !
- Mini-PCI Express !



Support:  [Specifications](#)

Scope of supply : Mainboard with CPU and heatsink.

- Intel Kaby Lake ULV Core i3/i5/i7 Processor
- Intel HD graphics and DirectX 12 support
- Dual channel DDR4 with two connectors for MAX. 32GB memory
- Support triple display for HDMI, DisplayPort and LVDS / eDP
- Features high speed Dual Gigabit Ethernet
- Features 1 SATA 6Gb/s
- Four SuperSpeed USB3.0 ports support
- Three RS232 + One RS232/422/485 ports
- One PCI Express Mini Card connector for expansion
- One M.2 2232 (E key) for expansion
- 8 V to 24 V wide-range voltage input

Item

Form Factor

Spec

3.5" single board computer, 102mm x 147mm (4" x 5.8")

Processor Chipset	Intel Kaby Lake-U i5-7300U with integrated graphics (Compatible with 3955U/i3-6100U/i5-6300U/i7-6600U and 3965U/i3-7100U/i7-7600U)	
Main Memory	2 x 260-pin DDR4 SO-DIMM slot - Max capacity up to 32GB	
Audio Controller	Realtek ALC283	
Expansion Capability	- M.2 2230 (E Key) with (PCIex1/USB2.0) 1 - Mini PCIe (full length, USB/PCIe/SATA) 1 - HDMI-out 1 - Display port 1	
External I/O	- USB3.0 4 - RJ-45 2 - Audio combo jack (Mic-in and Line-out) 1 - LVDS/eDP 1 7-pin SATA connector 1 4-pin SATA power 1 - USB2.0 2	
Internal I/O	- RS-232 3 - RS-232/422/485 1 - Audio header supporting system stereo speaker or buzzer 1 - MiAPI header 1 - Chassis front panel header 1	
SIO Controller	NCT6104D	
LAN Support	1 x I219LM, 1 x I211AT	
BIOS	AMI UEFI	
Hardware Management	- Nuvoton NCT6104D based subsystem, including: - Voltage sense to detect out of range power supply voltages - Thermal sense to detect out of range thermal values - Operating Temperature: 0°C ~ 60°C (32°F ~ 140°F)	
Environment	- Storage Temperature: -20°C ~ 80°C (-4°F ~ 140°F) - Relative Humidity: 95% @60°C non-condensing	
Certification	- CE - FCC	